

S-18 All Purpose Cement

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Revision Date: 10/03/2014

Date of issue: 01/10/2013

Supersedes Date: 01/10/2013

Version: 1.0

SECTION 1: IDENTIFICATION

1.1. Product Identifier

Product Form: Mixture

Product Name: S-18 All Purpose Cement

Synonyms: Polychloroprene Adhesive Blend/Compound

1.2. Intended Use of the Product No additional information available

1.3. Name, Address, and Telephone of the Responsible Party

Company

RH Products Co., Inc.

308 Old High Street

Acton, MA USA 01720

Information Telephone Number: 1-978-897-8000

1.4. Emergency Telephone Number

Emergency Number : 1-800-535-5053 INFOTRAC; 1-352-323-3500 INFOTRAC International

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the Substance or Mixture

Classification (GHS-US)

Flam. Liq. 2 H225

Skin Irrit. 2 H315

Eye Irrit. 2A H319

Skin Sens. 1 H317

Muta. 2 H341

Repr. 2 H361

STOT SE 3 H336

STOT RE 2 H373

2.2. Label Elements

GHS-US Labeling

Hazard Pictograms (GHS-US)



Signal Word (GHS-US)

: Danger

Hazard Statements (GHS-US)

: H225 - Highly flammable liquid and vapor.
H315 - Causes skin irritation.
H317 - May cause an allergic skin reaction.
H319 - Causes serious eye irritation.
H336 - May cause drowsiness or dizziness.
H341 - Suspected of causing genetic defects.
H361 - Suspected of damaging fertility or the unborn child.
H373 - May cause damage to organs through prolonged or repeated exposure.

Precautionary Statements (GHS-US)

: P201 - Obtain special instructions before use.
P202 - Do not handle until all safety precautions have been read and understood.
P210 - Keep away from heat, hot surfaces, open flames, sparks. - No smoking.
P233 - Keep container tightly closed.
P240 - Ground/bond container and receiving equipment.
P241 - Use explosion-proof electrical, lighting, ventilating equipment.
P242 - Use only non-sparking tools.
P243 - Take precautionary measures against static discharge.
P260 - Do not breathe vapors, mist, spray.
P264 - Wash hands, forearms, and exposed areas thoroughly after handling.
P271 - Use only outdoors or in a well-ventilated area.
P272 - Contaminated work clothing must not be allowed out of the workplace.
P280 - Wear eye protection, protective clothing, protective gloves.
P303+P361+P353+P352 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash with plenty of water.

S-18 All Purpose Cement

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P304+P340 - IF INHALED: Remove person to fresh air and keep at rest in a position comfortable for breathing.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

P308+P313 - If exposed or concerned: Get medical advice/attention.

P312 - Call a poison center if you feel unwell.

P321 - Specific treatment (see Section 4).

P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.

P337+P313 - If eye irritation persists: Get medical advice/attention.

P362+P364 - Take off contaminated clothing and wash it before reuse.

P370+P378 - In case of fire: Use dry chemical powder, alcohol-resistant foam, carbon dioxide (CO₂) to extinguish.

P391 - Collect spillage.

P403+P233 - Store in a well-ventilated place. Keep container tightly closed.

P235+P405 - Keep cool. Store locked up.

P501 - Dispose of contents/container according to local, regional, national, and international regulations.

2.3. Other Hazards

Aquatic Acute 1

Aquatic Chronic 1

H410 - Very toxic to aquatic life with long lasting effects.

P273 - Avoid release to the environment.



GHS09

2.4. Unknown Acute Toxicity (GHS-US)

No data available

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substance

Not applicable

3.2. Mixture

| Name | Product Identifier | % | Classification (GHS-US) |
|-------------------------|--------------------|------|---|
| n-Heptane | (CAS No) 142-82-5 | 34.7 | Flam. Liq. 2, H225 Skin Irrit. 2, H315 Eye Irrit. 2B, H320 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 |
| Toluene | (CAS No) 108-88-3 | 33 | Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361 STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Acute 2, H401 Aquatic Chronic 3, H412 |
| Proprietary Component A | Proprietary* | 15.2 | Muta. 2, H341 |
| Ethyl acetate | (CAS No) 141-78-6 | 8 | Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336 |
| Acetone | (CAS No) 67-64-1 | 5.3 | Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336 |
| Proprietary Component B | Proprietary* | 1.9 | Not classified |

S-18 All Purpose Cement

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| | | | |
|-------------------------|--------------|-----|--|
| Proprietary Component C | Proprietary* | 1.9 | Skin Irrit. 2, H315 Eye Irrit. 2A, H319 Skin Sens. 1B, H317 STOT SE 3, H335 |
|-------------------------|--------------|-----|--|

*The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.
Full text of H-phrases: see section 16

SECTION 4: FIRST AID MEASURES

4.1. Description of First Aid Measures

First-aid Measures General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

First-aid Measures After Inhalation: Using proper respiratory protection, immediately move the exposed person to fresh air. Assure fresh air breathing. Call a physician if symptoms occur.

First-aid Measures After Skin Contact: Remove contaminated clothing. Gently wash with plenty of soap and water followed by rinsing with water for at least 15 minutes. Call a POISON CENTER or doctor/physician if you feel unwell. Wash contaminated clothing before reuse.

First-aid Measures After Eye Contact: Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention.

First-aid Measures After Ingestion: Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER or doctor/physician.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/Injuries: Causes skin irritation. Causes serious eye irritation. Vapors may cause drowsiness and dizziness. Exposure may produce an allergic reaction.

Symptoms/Injuries After Inhalation: High concentration of vapours may induce: headache, dizziness, drowsiness, nausea and vomiting.

Symptoms/Injuries After Skin Contact: Causes skin irritation. May cause an allergic skin reaction. Repeated exposure may cause skin dryness or cracking.

Symptoms/Injuries After Eye Contact: Causes serious eye irritation.

Symptoms/Injuries After Ingestion: Ingestion is likely to be harmful or have adverse effects.

Chronic Symptoms: May cause damage to organs through prolonged or repeated exposure. May cause damage to central nervous system, liver, and kidneys. Suspected of damaging fertility or the unborn child. Suspected of causing genetic defects.

4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention.

SECTION 5: FIRE-FIGHTING MEASURES

5.1. Extinguishing Media

Suitable Extinguishing Media: Dry chemical powder, alcohol-resistant foam, carbon dioxide (CO₂).

Unsuitable Extinguishing Media: Do not use a heavy water stream. Use of heavy stream of water may spread fire.

5.2. Special Hazards Arising From the Substance or Mixture

Fire Hazard: Highly flammable liquid and vapor.

Explosion Hazard: May form flammable/explosive vapor-air mixture. Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries.

Reactivity: Reacts violently with oxidants causing fire and explosion hazard.

5.3. Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire.

Firefighting Instructions: Use water spray or fog for cooling exposed containers. Do not get water inside containers. Do not apply water stream directly at source of leak. Fight fire from safe distance and protected location.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection.

Other Information: Refer to Section 9 for flammability properties.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Use special care to avoid static electric charges. Keep away from heat/sparks/open flames/hot surfaces – No smoking. Do not get in eyes, on skin, or on clothing. Do not breathe vapour or mist.

6.1.1. For Non-emergency Personnel

Protective Equipment: Use appropriate personal protection equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel.

6.1.2. For Emergency Responders

Protective Equipment: Equip cleanup crew with proper protection.

S-18 All Purpose Cement

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Emergency Procedures: Ventilate area. Eliminate ignition sources. Stop leak if safe to do so.

6.2. Environmental Precautions

Prevent entry to sewers and public waters.

6.3. Methods and Material for Containment and Cleaning Up

For Containment: Absorb and/or contain spill with inert material, then place in suitable container. Do not take up in combustible material such as: saw dust or cellulosic material.

Methods for Cleaning Up: Clear up spills immediately and dispose of waste safely. Use only non-sparking tools.

6.4. Reference to Other Sections

See heading 8, Exposure Controls and Personal Protection. Concerning disposal elimination after cleaning, see item 13.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for Safe Handling

Additional Hazards When Processed: Handle empty containers with care because residual vapors are flammable.

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking, or smoking and again when leaving work.

7.2. Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures: Proper grounding procedures to avoid static electricity should be followed.

Storage Conditions: Store in a dry, cool, well-ventilated place. Keep container closed when not in use. Keep in fireproof place.

Incompatible Products: Strong acids. Strong bases. Strong oxidizers.

7.3. Specific End Use(s) No additional information available

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control Parameters

| Toluene (108-88-3) | | |
|--------------------------|--|------------------------|
| USA ACGIH | ACGIH TWA (ppm) | 20 ppm |
| USA NIOSH | NIOSH REL (TWA) (mg/m ³) | 375 mg/m ³ |
| USA NIOSH | NIOSH REL (TWA) (ppm) | 100 ppm |
| USA NIOSH | NIOSH REL (STEL) (mg/m ³) | 560 mg/m ³ |
| USA NIOSH | NIOSH REL (STEL) (ppm) | 150 ppm |
| USA IDLH | US IDLH (ppm) | 500 ppm |
| USA OSHA | OSHA PEL (TWA) (ppm) | 200 ppm |
| USA OSHA | OSHA PEL (Ceiling) (ppm) | 300 ppm |
| Acetone (67-64-1) | | |
| USA ACGIH | ACGIH TWA (ppm) | 500 ppm |
| USA ACGIH | ACGIH STEL (ppm) | 750 ppm |
| USA NIOSH | NIOSH REL (TWA) (mg/m ³) | 590 mg/m ³ |
| USA NIOSH | NIOSH REL (TWA) (ppm) | 250 ppm |
| USA IDLH | US IDLH (ppm) | 2500 ppm (10% LEL) |
| USA OSHA | OSHA PEL (TWA) (mg/m ³) | 2400 mg/m ³ |
| USA OSHA | OSHA PEL (TWA) (ppm) | 1000 ppm |
| n-Heptane (142-82-5) | | |
| USA ACGIH | ACGIH TWA (ppm) | 400 ppm |
| USA ACGIH | ACGIH STEL (ppm) | 500 ppm |
| USA NIOSH | NIOSH REL (TWA) (mg/m ³) | 350 mg/m ³ |
| USA NIOSH | NIOSH REL (TWA) (ppm) | 85 ppm |
| USA NIOSH | NIOSH REL (ceiling) (mg/m ³) | 1800 mg/m ³ |
| USA NIOSH | NIOSH REL (ceiling) (ppm) | 440 ppm |
| USA IDLH | US IDLH (ppm) | 750 ppm |
| USA OSHA | OSHA PEL (TWA) (mg/m ³) | 2000 mg/m ³ |
| USA OSHA | OSHA PEL (TWA) (ppm) | 500 ppm |
| Ethyl acetate (141-78-6) | | |
| USA ACGIH | ACGIH TWA (ppm) | 400 ppm |
| USA NIOSH | NIOSH REL (TWA) (mg/m ³) | 1400 mg/m ³ |
| USA NIOSH | NIOSH REL (TWA) (ppm) | 400 ppm |
| USA IDLH | US IDLH (ppm) | 2000 ppm (10% LEL) |
| USA OSHA | OSHA PEL (TWA) (mg/m ³) | 1400 mg/m ³ |
| USA OSHA | OSHA PEL (TWA) (ppm) | 400 ppm |

S-18 All Purpose Cement

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

8.2. Exposure Controls

Appropriate Engineering Controls

: Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Gas detectors should be used when flammable gases/vapors may be released. Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapor or mists below the applicable workplace exposure limits indicated above. All electrical equipment should comply with the National Electric Code. Ensure all national/local regulations are observed.

Personal Protective Equipment

: Full protective flameproof clothing. Protective goggles. Gloves. Insufficient ventilation: wear respiratory protection.



Materials for Protective Clothing

: Wear fire/flame resistant/retardant clothing.

Hand Protection

: Wear chemically resistant protective gloves.

Eye Protection

: Chemical goggles or safety glasses.

Skin and Body Protection

: Wear suitable protective clothing.

Respiratory Protection

: Use NIOSH-approved air-purifying or supplied-air respirator where airborne concentrations of vapor or mist are expected to exceed exposure limits.

Other Information

: When using, do not eat, drink or smoke.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on Basic Physical and Chemical Properties

| | |
|--|---|
| Physical State | : Liquid |
| Appearance | : Off White Color |
| Odor | : Characteristic Solvent Odor |
| Odor Threshold | : No data available |
| pH | : No data available |
| Evaporation Rate | : No data available |
| Melting Point | : No data available |
| Freezing Point | : No data available |
| Boiling Point | : > 35 °C (95.00 °F) |
| Flash Point | : -7.78 °C ASTM D-56 9/21/2008 (18.00 °F) |
| Auto-ignition Temperature | : No data available |
| Decomposition Temperature | : No data available |
| Flammability (solid, gas) | : No data available |
| Vapor Pressure | : 180 mm Hg at 20 °C (68 °F) |
| Relative Vapor Density at 20 °C | : > 1 (heavier than air) |
| Relative Density | : 0.87 (water = 1) |
| Solubility | : Insoluble in water. |
| Partition Coefficient: N-octanol/water | : No data available |
| Viscosity | : No data available |
| Lower Flammable Limit | : 1 % |
| Upper Flammable Limit | : 12 % |

9.2. Other Information

VOC content : 75.7 % (5.32 lbs/gal or 638 g/l)

SECTION 10: STABILITY AND REACTIVITY

- 10.1. Reactivity:** Reacts violently with oxidants causing fire and explosion hazard.
- 10.2. Chemical Stability:** Stable under recommended handling and storage conditions (see section 7).
- 10.3. Possibility of Hazardous Reactions:** Hazardous polymerization will not occur.
- 10.4. Conditions to Avoid:** Direct sunlight. Extremely high or low temperatures. Open flame. Ignition sources.
- 10.5. Incompatible Materials:** Strong acids. Strong bases. Strong oxidizers.
- 10.6. Hazardous Decomposition Products:** Carbon oxides (CO, CO₂).

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information On Toxicological Effects

Acute Toxicity: Not classified

S-18 All Purpose Cement

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| | |
|---------------------------------|---|
| Toluene (108-88-3) | |
| LD50 Oral Rat | 5580 mg/kg |
| LD50 Dermal Rabbit | 8390 mg/kg |
| ATE (Vapors) | 25.70 mg/l/4h |
| Acetone (67-64-1) | |
| LD50 Oral Rat | 5800 mg/kg |
| LD50 Dermal Rabbit | 15688 mg/kg |
| LC50 Inhalation Rat | 44 g/m ³ |
| n-Heptane (142-82-5) | |
| LD50 Oral Rat | > 5000 mg/kg |
| LD50 Dermal Rabbit | 3000 mg/kg |
| LC50 Inhalation Rat | 103 g/m ³ (Exposure time: 4 h) |
| Ethyl acetate (141-78-6) | |
| LD50 Oral Rat | 5620 mg/kg |
| LD50 Dermal Rabbit | > 20 ml/kg |
| Proprietary Component A | |
| LD50 Oral Rat | > 40 g/kg |

Skin Corrosion/Irritation: Causes skin irritation.

Serious Eye Damage/Irritation: Causes serious eye irritation.

Respiratory or Skin Sensitization: May cause an allergic skin reaction.

Germ Cell Mutagenicity: Suspected of causing genetic defects.

Carcinogenicity: Not classified

| | |
|--------------------------------|---|
| Toluene (108-88-3) | |
| IARC group | 3 |
| Proprietary Component A | |
| IARC group | 3 |

Reproductive Toxicity: Suspected of damaging fertility or the unborn child.

Specific Target Organ Toxicity (Single Exposure): May cause drowsiness or dizziness.

Specific Target Organ Toxicity (Repeated Exposure): May cause damage to organs through prolonged or repeated exposure.

Aspiration Hazard: Not classified

Symptoms/Injuries After Inhalation: High concentration of vapours may induce: headache, dizziness, drowsiness, nausea and vomiting.

Symptoms/Injuries After Skin Contact: Causes skin irritation. May cause an allergic skin reaction. Repeated exposure may cause skin dryness or cracking.

Symptoms/Injuries After Eye Contact: Causes serious eye irritation.

Symptoms/Injuries After Ingestion: Ingestion is likely to be harmful or have adverse effects.

Chronic Symptoms: May cause damage to organs through prolonged or repeated exposure. May cause damage to central nervous system, liver, and kidneys. Suspected of damaging fertility or the unborn child. Suspected of causing genetic defects.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecology - General : Very toxic to aquatic life with long lasting effects.

| | |
|-----------------------------|--|
| Toluene (108-88-3) | |
| LC50 Fish 1 | 15.22 - 19.05 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through]) |
| EC50 Daphnia 1 | 5.46 - 9.83 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static]) |
| LC 50 Fish 2 | 12.6 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static]) |
| EC50 Daphnia 2 | 11.5 mg/l (Exposure time: 48 h - Species: Daphnia magna) |
| NOEC chronic crustacea | 0.74 mg/l (Ceriodaphnia dubia) |
| Acetone (67-64-1) | |
| LC50 Fish 1 | 4144.846 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss) |
| EC50 Daphnia 1 | 1679.66 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static]) |
| LC 50 Fish 2 | 6210 (6210 - 8120) mg/l (Exposure time: 96 h - Species: Pimephales promelas [static]) |
| EC50 Daphnia 2 | 12600 (12600 - 12700) mg/l (Exposure time: 48 h - Species: Daphnia magna) |
| n-Heptane (142-82-5) | |
| LC50 Fish 1 | 375.0 mg/l (Exposure time: 96 h - Species: Cichlid fish) |

S-18 All Purpose Cement

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| Ethyl acetate (141-78-6) | |
|--------------------------|--|
| LC50 Fish 1 | 220 - 250 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through]) |
| EC50 Daphnia 1 | 560 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static]) |
| LC 50 Fish 2 | 484 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [flow-through]) |

12.2. Persistence and Degradability

| Acetone (67-64-1) | |
|-------------------------------|---------------------------------|
| Persistence and Degradability | Readily biodegradable in water. |

12.3. Bioaccumulative Potential

| Toluene (108-88-3) | |
|--------------------|------|
| Log Pow | 2.65 |

| Acetone (67-64-1) | |
|-------------------|-------|
| BCF fish 1 | 0.69 |
| Log Kow | -0.24 |

| n-Heptane (142-82-5) | |
|----------------------|------|
| Log Pow | 4.66 |

| Ethyl acetate (141-78-6) | |
|--------------------------|-----|
| BCF fish 1 | 30 |
| Log Pow | 0.6 |

12.4. Mobility in Soil No additional information available

12.5. Other Adverse Effects

Other Information : Avoid release to the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste Disposal Recommendations: Dispose of waste material in accordance with all local, regional, national, and international regulations.

Additional Information: Handle empty containers with care because residual vapors are flammable. RCRA Waste Number: D001.

SECTION 14: TRANSPORT INFORMATION

14.1. In Accordance with DOT

Proper Shipping Name : ADHESIVES containing a flammable liquid
Hazard Class : 3
Identification Number : UN1133
Label Codes : 3
Packing Group : II
ERG Number : 128



14.2. In Accordance with IMDG

Proper Shipping Name : ADHESIVES
Hazard Class : 3
Identification Number : UN1133
Packing Group : II
Label Codes : 3
EmS-No. (Fire) : F-E
EmS-No. (Spillage) : S-D
MFAG Number : 127
Marine Pollutant : Yes



14.3. In Accordance with IATA

Proper Shipping Name : ADHESIVES
Packing Group : II
Identification Number : UN1133
Hazard Class : 3
Label Codes : 3
ERG Code (IATA) : 3L



S-18 All Purpose Cement

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 15: REGULATORY INFORMATION

15.1 US Federal Regulations

| | |
|---|--|
| S-18 All Purpose Cement | |
| SARA Section 311/312 Hazard Classes | Fire hazard Immediate (acute) health hazard Delayed (chronic) health hazard |
| Toluene (108-88-3) | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory Listed on United States SARA Section 313 | |
| RQ (Reportable quantity, section 304 of EPA's List of Lists) : | 1000 lb |
| SARA Section 313 - Emission Reporting | 1.0 % |
| Acetone (67-64-1) | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory | |
| EPA TSCA Regulatory Flag | T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA. |
| n-Heptane (142-82-5) | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory | |
| EPA TSCA Regulatory Flag | T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA. |
| Ethyl acetate (141-78-6) | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory | |
| EPA TSCA Regulatory Flag | T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA. |
| Proprietary Component A | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory | |
| Proprietary Component B | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory | |
| Proprietary Component C | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory | |

15.2 US State Regulations

| | |
|--|--|
| Toluene (108-88-3) | |
| U.S. - California - Proposition 65 - Developmental Toxicity | WARNING: This product contains chemicals known to the State of California to cause birth defects. |
| U.S. - California - Proposition 65 - Reproductive Toxicity - Female | WARNING: This product contains chemicals known to the State of California to cause (Female) reproductive harm. |
| Toluene (108-88-3) | |
| U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List U.S. - Pennsylvania - RTK (Right to Know) List | |
| Acetone (67-64-1) | |
| U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List U.S. - Pennsylvania - RTK (Right to Know) List | |
| n-Heptane (142-82-5) | |
| U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List | |
| Ethyl acetate (141-78-6) | |
| U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List U.S. - Pennsylvania - RTK (Right to Know) List | |

SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Revision Date : 10/03/2014

S-18 All Purpose Cement

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Other Information : This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.

GHS Full Text Phrases:

| | |
|-------------------|---|
| Aquatic Acute 1 | Hazardous to the aquatic environment - Acute Hazard Category 1 |
| Aquatic Acute 2 | Hazardous to the aquatic environment - Acute Hazard Category 2 |
| Aquatic Chronic 1 | Hazardous to the aquatic environment - Chronic Hazard Category 1 |
| Aquatic Chronic 3 | Hazardous to the aquatic environment - Chronic Hazard Category 3 |
| Asp. Tox. 1 | Aspiration hazard Category 1 |
| Eye Irrit. 2A | Serious eye damage/eye irritation Category 2A |
| Eye Irrit. 2B | Serious eye damage/eye irritation Category 2B |
| Flam. Liq. 2 | Flammable liquids Category 2 |
| Muta. 2 | Germ cell mutagenicity Category 2 |
| Repr. 2 | Reproductive toxicity Category 2 |
| Skin Irrit. 2 | Skin corrosion/irritation Category 2 |
| Skin Sens. 1 | Skin sensitization Category 1 |
| Skin Sens. 1B | Skin sensitization Category 1B |
| STOT RE 2 | Specific target organ toxicity (repeated exposure) Category 2 |
| STOT SE 3 | Specific target organ toxicity (single exposure) Category 3 |
| STOT SE 3 | Specific target organ toxicity (single exposure) Category 3 |
| H225 | Highly flammable liquid and vapor |
| H304 | May be fatal if swallowed and enters airways |
| H315 | Causes skin irritation |
| H317 | May cause an allergic skin reaction |
| H319 | Causes serious eye irritation |
| H320 | Causes eye irritation |
| H335 | May cause respiratory irritation |
| H336 | May cause drowsiness or dizziness |
| H341 | Suspected of causing genetic defects |
| H361 | Suspected of damaging fertility or the unborn child |
| H373 | May cause damage to organs through prolonged or repeated exposure |
| H400 | Very toxic to aquatic life |
| H401 | Toxic to aquatic life |
| H410 | Very toxic to aquatic life with long lasting effects |
| H412 | Harmful to aquatic life with long lasting effects |

The information above is believed to be accurate and represents the information currently available to us. We however, make no warranty of merchantability or any other warranty, express or implied, with respect to this information, and we assume no liability resulting from its use.

SDS US (GHS HazCom)