

Material Safety Data Sheet
 May be used to comply with
 OSHA's Hazard Communication Standard,
 29 CFR 1910.1200. Standard must be
 consulted for specific requirements.

U.S. Department of Labor
 Occupational Safety and Health Administration
 (Non-Mandatory Form)
 Form Approved
 OMB No. 1218-0072



IDENTITY (As Used on Label and List)
 PUMIE SCOURING STICK

Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.

Section I

Manufacturer's Name UNITED STATES PUMICE CO.	Emergency Telephone Number (818) 882-0300
Address (Number, Street, City, State, and ZIP Code) 20219 BAHAMA STREET	Telephone Number for Information (818) 882-0300
CHATSWORTH, CA. 91311	Date Prepared
	Signature of Preparer (optional)

Section II — Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity; Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	% (optional)
PUMICE (VOLCANIC GLASS)				
THERE IS NO FREE CRYSTALLINE SILICA PRESENT				

Section III — Physical/Chemical Characteristics

Boiling Point	N.A.	Specific Gravity (H ₂ O = 1)	N.A.
Vapor Pressure (mm Hg.)	N.A.	Melting Point	2390° F
Vapor Density (AIR = 1)	N.A.	Evaporation Rate (Butyl Acetate = 1)	N.A.
Solubility in Water	NOT SOLUBLE		
Appearance and Odor	ODORLESS SOLID		

Section IV — Fire and Explosion Hazard Data

Flash Point (Method Used)	N.A.	Flammable Limits	N.A.	LEL	N.A.	UEL	N.A.
Extinguishing Media	N.A.						
Special Fire Fighting Procedures	NONE						
Unusual Fire and Explosion Hazards	NONE						

Section V — Reactivity Data

Stability	Unstable		Conditions to Avoid
	Stable	X	NONE
Incompatibility (Materials to Avoid)			NONE
Hazardous Decomposition or Byproducts			
NONE			
Hazardous Polymerization	May Occur		Conditions to Avoid
	Will Not Occur	X	NONE

Section VI — Health Hazard Data

Route(s) of Entry:	Inhalation?	YES	Skin?	NO	Ingestion?	YES
Health Hazards (Acute and Chronic)						
DRY SAWING OR GRINDING MAY RESULT IN THE RELEASE OF DUST PARTICLES WHICH, ACUTE, MAY CAUSE IRRITATION OF EYES, NOSE OR THROAT AND CHRONIC MAY RESULT IN LUNG DISEASE (SILICOSIS) IF EXPOSED FOR PROLONGED T						
Carcinogenicity:	NTP?	NO	IARC Monographs?	NO	OSHA Regulated?	NO

Signs and Symptoms of Exposure IRRITATION OF EYES, NOSE & THROAT OR SHORTNESS OF BREATH

Medical Conditions Generally Aggravated by Exposure PRE EXISTING LUNG DISEASE SUCH AS EMPHYSEMA OR ASTHMA.

Emergency and First Aid Procedures IRRIGATE EYES GENEROUSLY WITH CLEAN WATER FOR 15 MIN. IF IRRITATION PERSISTS, CALL A PHYSICIAN.

Section VII — Precautions for Safe Handling and Use

Steps to Be Taken in Case Material Is Released or Spilled

SWEEP UP AND PROPERLY DISPOSE

Waste Disposal Method DISPOSE AS COMMON WASTE

Precautions to Be Taken in Handling and Storing NONE

Other Precautions WEAR NIOSH APPROVED RESPIRATOR AND TIGHT FITTING GOGGLES WHEN DRY SAWING OR GRINDING, OR SAW & GRIND WHEN WET

Section VIII — Control Measures (WHEN SAWING OR GRINDING)

Respiratory Protection (Specify Type) NIOSH APPROVED PARTICULATE RESPIRATOR

Ventilation	Local Exhaust		Special
	Mechanical (General)	IN CONFINED AREA	Other
Protective Gloves	WHEN REQUIRED	Eye Protection	TIGHT FITTING GOGGLES
Other Protective Clothing or Equipment NONE			
Work/Hygienic Practices N.A.			